

VHF/UHF Imagery of Targets, Decoys, and Trees

A. J. Gatesman, C. Beaudoin, R. Giles, J. Waldman Submillimeter-Wave Technology Laboratory University of Massachusetts Lowell

J.L. Poirier, K.-H. Ding, P. Franchi, E.J. Tichovolsky, and B. Weijers

Air Force Research Laboratory

Hanscom Air Force Base, MA 01730

W. Nixon

U.S. Army National Ground Intelligence Center
Charlottesville, VA 22902





maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	ion of information. Send comments is arters Services, Directorate for Infor	regarding this burden estimate mation Operations and Reports	or any other aspect of the 1215 Jefferson Davis	is collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE OCT 2002		2. REPORT TYPE		3. DATES COVERED 00-00-2002 to 00-00-2002		
4. TITLE AND SUBTITLE		5a. CONTRACT NUMBER				
VHF/UHF Imagery of Targets, Decoys, and Trees				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Massachusetts Lowell, Submillimeter-Wave Technology Laboratory, 175 Cabot Street, Lowell, MA, 01854				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited						
13. SUPPLEMENTARY NO The original docum	otes nent contains color i	mages.				
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ADSTRACT	19	RESPONSIBLE PERSON	

Report Documentation Page

Form Approved OMB No. 0704-0188



Physical Scale Modeling Radar Measurements

• The entire VHF/UHF band can be modeled with a 2-18 GHz radar system and carefully constructed scale models and scenes

VHF: 25 MHz - 100 MHz (using 2-8 GHz and 1/87th scale models)

VHF/UHF: **100 MHz - 500 MHz** (using: 3.5-17.5 GHz and 1/35th scale models)

UHF: **300 MHz - 1000 MHz** (using: 4.8-16 GHz and 1/16th scale models)

Advantages of Scale Modeling Radar Measurements:


- Rapidly generate calibrated signature libraries
- Controlled, covert environment
- Models built from intelligence data
- Rough ground planes, clutter, trees







Fully-Polarimetric Radar Range




- 2 GHz 18 GHz Pulsed-cw Radar System
- Accurate Positioning of Target, Scene, and Calibration Objects
- Pulsing Unit Controls Polarization for Fully-Polarimetric Operation








University of Massachusetts Lowell 1/35th Scale Vehicles, Terrain and **Trees**














Signature Validation with 1/16th Scale Slicy













VHF RCS of Slicy Compared with CARLOS

285.7 MHz and 15° elevation














Materials Issues


- •VHF/UHF dielectric constant of wood ranges from $\varepsilon = 13 + i \ 3$ to $68 + i \ 20$ Scale model wood (aluminum-loaded epoxy): $\varepsilon = 69 + i \cdot 10$
 - •VHF/UHF dielectric constant of soil ranges from $\varepsilon = 3 + i 0.5$ to 24 + i 5Scale model soil (carbon-loaded polyurethane): $\varepsilon = 14.7 + i 1.1$

Reflectivity of 1/35th Scale M-1 Coating



- 4000 Å sputtered Cu coating on M-1 model
- Skin depth of Cu film at 10 GHz = 8000 Å






• Brewster angle of soil = 15° elev.







Demonstration of Brewster's Angle at 286 MHz



- Dihedral formed between aluminum block and ground plane to demonstrate Brewster's angle
- Ground plane dielectric constant: 14.7 i 1.1
- Ground plane models soil with moderate moisture content







VHF/UHF TRCS of M-1 Tank

Free-space


VHF/UHF Radar Cross Section of M-1 Tank in Free Space



On smooth ground plane

VHF/UHF Radar Cross Section of M-1 Tank on Ground Plane

frequency-averaged geometric median, 200-371 MHz, 45° elevation










VHF/UHF TRCS of M-1 Tank


On ground plane with trees

VHF/UHF Radar Cross Section of M-1 Tank on Ground Plane with Trees



Trees only

VHF/UHF Radar Cross Section of 8 Trees on Ground Plane










Imagery of 8 Trees on Smooth Ground Plane






HH

VH

Imagery of M1 Tank in Open Field








HH

VH

Imagery of T-72 Tank in Open Field








HH

VH


Imagery of Tank Decoy in Open Field








Massachusett Imagery of M1 Tank Obscured by Trees






Massachuse Timagery of T-72 Tank Obscured by Trees






Massachuretts Lowell Tmagery of Tank Decoy Obscured by Trees





UHF & W-band Imagery of BMP-2

Free-space, 40° elevation, Image center angle 55° UHF and W-Band Bandwidth: 487.5 MHz --> 0.31 (m) down range resolution UHF aperture 75 deg --> 0.31 (m) cross range resolution W-Band aperture 0.288 deg --> 0.31 (m) cross range resolution







Program Accomplishments

- Established Fully-Polarimetric Pulsed-cw 2-18 GHz Radar Range
- Acquired Calibrated VHF/UHF Signatures of Scale Models in Forested Terrain
- Demonstrated Signature Validation with MoM Code (CARLOS)
- Developed Signal Processing Techniques for FOPEN ISAR Imaging
- Developed Dielectrics to Model Live Wood
- Fabricated Ground Planes Modeling Smooth, Moist Soil Surface



